

## Infocus X17 DLP Projector 2300 ANSI XGA [Discontinued]

Model: [X17](#)

Price per Unit (piece): SGD \$959.00



**Discontinued Product** This item has been discontinued by the manufacturer or vendor and is no longer available for purchase. Thank you.

### Infocus X17 DLP Projector 2300 ANSI XGA

Model: X17

Resolution: 1024 x 768 XGA

Brightness: 2300 ANSI Lumen

Weight: 2.4 kg

The search for a steady-performing, reliable projector ends here and it is completely affordable. The X17 features 2300 Max ANSI Lumens and an 2000:1 contrast ratio which equates to bright images with lush color saturation and deep black levels, even in meeting spaces with present ambient light. The X17 utilizes the latest BrilliantColor™ technology to output true-to-life colors and shades through a wide, short throw lens, providing big image flexibility to smaller rooms.

Display	
Native Aspect Ratio:	4x3
Supported Aspect Ratio:	16:9, 4:3, 5:4

<b>Brightness: (max ANSI lumens)</b>	<b>High Bright: 2300 Lumens Eco Mode: 1900 Lumens</b>
Contrast Ratio:	2000 : 1 Full On/Full Off
Display Technology:	DLP by Texas Instruments: 0.55" LVDS with Brilliant Color
Data Compatibility:	VGA (640x480), SVGA (800x600), XGA (1024x768), SXGA (1280x1024), SXGA+ (1400x1050)
Video Compatibility:	Full NTSC, PAL, SECAM, 480i, 576i, 480p, 576p, 720p, 1080i
Color Wheel (DLP Only):	6-segment (RGBYCW)
<b>Native Resolution:</b>	<b>XGA</b>
Projector Placement:	Ceiling Projection, Front Projection, Rear Projection
SMPTE Brightness:	Not Available
Lamp Wattage:	High Bright: Not Available Eco Mode: 140 Watts
Lamp Life:	High Bright: Not Available Eco Mode: 4000 Hours
Minimum Image Size:	2.25 ft (0.69 m)
Maximum Image Size:	21 ft (6.4 m)
Standard Lens Zoom:	1.1 : 1
Standard Lens Throw Ratio:	1.9 - 2.1 (Distance/Width)
Standard Lens Image Offset Ratio:	120%
Standard Lens Projection Distance:	4.9 - 19.68 ft (1.49 - 6 m)
Digital Keystone Correction (Vertical):	+30°/-30°
Digital Keystone Correction (Horizontal):	Not Available
Lens Shift:	Not Available
<b>Inputs and Outputs</b>	
DVI:	Not Available
M1:	Not Available
HDMI:	Not Available
BNC:	Not Available
Component (RCA):	<b>Number of Inputs: 0</b> 480i/480p/576i/756p/720p/1080i requires optional VESA to Component adapter cable.
VESA (HD15):	<b>Number of Inputs: 1</b> 15-pin analog
S-Video:	<b>Number of Inputs: 1</b> 4-pin mini-DIN
Composite (RCA):	<b>Number of Inputs: 1</b>
Standard Definition TV:	Composite RCA, S-Video
Enhanced Definition TV:	VGA
High Definition TV:	VGA
Computer:	VGA
HDCP Support:	No
Stereo RCA Jacks Inputs:	No

Stereo 3.5 mm Mini-jack Inputs:	Yes
12v trigger for motorized screens (3.5 mm mini-jack):	No
Projector Control:	Projector Keypad, Remote, RS-232
Speakers:	5.0 Watt mono speaker
Monitor Output:	Yes
Audio Output:	Not Available
<b>Compatibility</b>	
Data Compatibility:	VGA (640x480), SVGA (800x600), XGA (1024x768), SXGA (1280x1024), SXGA+ (1400x1050)
H-Sync Range:	31.35 - 68.7kHz
V-Sync Range:	56 - 85Hz
Video Compatibility:	Full NTSC, PAL, SECAM, 480i, 576i, 480p, 576p, 720p, 1080i
<b>General</b>	
Audible Noise:	29 dB
Actual Dimensions:	<b>Height:</b> 4.4 in (11.18 cm) <b>Length:</b> 10.39 in (26.39 cm) <b>Width:</b> 8.8 in (22.35 cm)
<b>Actual Weight:</b>	<b>5.3 lbs (2.4 kg)</b>
Shipping Dimensions:	Not Available
Shipping Weight:	Not Available
Operating temperature: (at sea level)	41 - 95° F (5 - 35° C)
Maximum Altitude Supported:	Not Available
Typical Power Consumption:	285 Watts
Maximum Power Consumption:	Not Available
Power Supply:	100 - 240 Volts at 50 - 60 Hz
Menu Languages:	English, French, German, Italian, Norwegian, Portuguese, Simplified Chinese, Spanish, Russian, Swedish, Danish, Turkish, Polish, Finnish, Dutch
Approvals:	UL and c-UL (US/Canada), FCC (US/Canada), CE (CE member countries), GOST (Russia), CCC (China), PSB, MIC, EK

**Warranty: 2 years on-site projector warranty.  
180 days Lamp warranty.**